

BUILDING

INDUSTRY

ELEVATORS

WIND POWER

LM 90 - LM 250

I MATERIAL LIFTING - ELECTRIC HOIST

PRODUCT OF FRANCE
MANUFACTURED IN FRANCE



CONVENIENCE

- ✓ Adapts to all construction sites
- ✓ No limitation of working height
- ✓ Compatible with a household electrical outlet
- ✓ Possibility of doubling the load capacity by using a reeving kit (double rope kit) - *(on option)*



SAFETY

- ✓ Two travel end stoppers to halt ascents and/or descents
- ✓ Electric motor protected by a temperature probe in case of overheating



COMFORT

- ✓ Portable and easy to handle (storage box supplied with the hoist)
- ✓ Compact and lightweight
- ✓ Pendant control or Wireless Remote Control - *(on option)*



Versatile and Universal

The LM passing wire rope hoist enables to lift equipment with a load capacity of 90 kg and 250 kg.

The LM hoist can be used on all types of work sites, in the worldwide; in the building sector for hoisting and hauling equipment, in the elevator sector for the transport of equipment inside the shafts, in the wind energy sector for maintenance works.

Sturdy and Efficient

Machined in the mass, the LM hoist is made up of a 100 % aluminum outer walls. This makes it lightweight, compact, as well as resistant to corrosion. It is equipped with a temperature probe that protects the electric motor and stops the hoist in case of overheating.

For more information:

www.fixator.com



FIXATOR
SAFETY AT THE VERY TOP

MANUFACTURER OF HEIGHT ACCESS FOR 95 YEARS

BUILDING

INDUSTRY

ELEVATORS

WIND POWER

LM 90 - LM 250

I MATERIAL LIFTING - ELECTRIC HOIST

■ ■ PRODUCT OF FRANCE
MANUFACTURED IN FRANCE

✓ TECHNICAL SPECIFICATIONS



DID YOU KNOW ?

The first LM was designed in the 80s. Originally, it was destined for Elevators sector, but it quickly went beyond its favorite sector.

Today, LM is used on all types of worksites in different fields of activity. Its age and versatility are quality guarantees for users.

Description	LM 90	LM 250
Max. Direct Working Load/WLL (kg)	90	250
Max. Reeved Working Load/WLL (kg)	180	500
Motor power (kW)	0,45	0,45
Voltage (V)	Single phase 230 V - 50Hz - 3.5 A	Single phase 230 V - 50Hz - 3.5 A
Climbing speed (m/min)	17	6
Hoist weight (kg)	19	19
Cable diameter (mm)	5	5
Upper travel end stopper	yes	
Lower travel end stopper	yes	

✓ STANDARD EQUIPMENT

- I Storage box
- I Pendant control (2.5m of wire)
- I Suspension hook
- I 2 travel end stoppers (upper and lower)



✓ ACCESSORIES

- I Wireless Remote control
- I Double rope kit (reeving kit)
- I Extension for pendant control (from 5 to 60m)



FIXATOR
SAFETY AT THE VERY TOP

8 rue du Bois Rinier - P.A. - BP 10041
49181 St-Barthélemy-d'Anjou Cedex
FRANCE

T. : + 33 (0) 241 311 700
Fax : + 33 (0) 241 311 705

Email : info@fixator.com
www.fixator.com

